

# Allen-Bradley Flange Mounted Disconnects and Circuit Breakers

Flange Mounted Operator Handle and Operating Mechanisms, variable depth and cable operated. The D1 Cutout detail is the standard cutout in all Stock SCE enclosures.

\*The exception is part numbers with the Letter *U* at the end (Example: SCE-84XM4018U), this indicates the Universal Cutout (D7).

Adapter Kits available for use with Universal cutout, for D2 cutout: SCE-UA400V and for D1 cutout: SCE-UAV.

Enclosures can be ordered with the specific cutout to fit your application through our CSE program.

HANDLE / OPERATOR	CUTOUT DETAIL	HANDLE / OPERATOR	CUTOUT DETAIL	HANDLE / OPERATOR	CUTOUT DETAIL
140G	D1	1494F-P1	D1	1494V-H2	D2
140RC	D1	1494F-P2	D1	1494V-H5	D1
140U	D1	1494F-S1	D1	1494V-H8	D2
1494C < 400 AMP	D1	1494F-S2	D2	1494V-M1	D1
1494C 400, 600 AMP	D2	1494FU-HS1	D1	1494V-M2	D2
1494F-200	D7	1494M-NF200	D6	1494V-R1	D14
1494F-N100	D7	1494U	D1	1494V-R2	D15
1494F-N30	D7	1494U-HM1	D1	1494V-W10	D1
1494F-N60	D7	1494U-HP1	D1	1494V-W2	D2
1494F-M1	D1	1494U-HS1	D1	1494V-W5	D1
1494F-M2	D2	1494V-H10	D1	1494V-W8	D2

