

Siemens Flange Mounted Disconnects and Circuit Breakers

Flange Mounted Operator Handle and Operating Mechanisms, variable depth and cable operated. The D1 Cutout detail is the standard cutout in all Stock SCE enclosures.

*The exception is part numbers with the Letter *U* at the end (Example: SCE-84XM4018U), this indicates the Universal Cutout (D7).

Adapter Kits available for use with Universal cutout, for D2 cutout: SCE-UA400V and for D1 cutout: SCE-UAV.

Enclosures can be ordered with the specific cutout to fit your application through our CSE program.

HANDLE / OPERATOR	CUTOUT DETAIL
FDH10	D1
FDH104	D1
FDH20	D1
FDH204	D1
FDS06L	D1
FDS06R	D1
FDS20L	D1
FDS20R	D1
FHOH	D1
FHOH4	D1
FHOHN	D2
FHOHN4	D2
MFHM3R	D1

HANDLE / OPERATOR	CUTOUT DETAIL
MFHM3RB	D1
MFHM3RS	D1
MFHM3RSB	D1
MFHM4X	D1
MFHP3RS	D2
MFHP3RSB	D2
MFHP4X	D2
MFKF3R	D1
VBH1	D1
VBH14X	D1
VBH2	D2
VBH24X	D2
VBH2R	D2

