

GASKET PERFORMANCE CHARACTERISTICS

	SCE STANDARD		FOR REFERENCE ONLY		
	Strip Gasket Urethane Sponge Rubber	Pour-In-Place Gasket Urethane Sponge Rubber	Neoprene Sponge Rubber	Silicone Sponge Rubber	Viton Sponge Rubber
	10 LBS / 15LBS	10 LBS / 15LBS	10 LBS / 15LBS	10 LBS / 15LBS	10 LBS / 15LBS
Cold Flexability	EXCELLENT	EXCELLENT	EXCELLENT	EXCELLENT	EXCELLENT
Stain Resistance	GOOD	GOOD	POOR	EXCELLENT	GOOD
Compression Set	EXCELLENT	EXCELLENT	POOR	EXCELLENT	EXCELLENT
Heat Resistance 220°	GOOD	GOOD	POOR	EXCELLENT	EXCELLENT
Uv Resistance	EXCELLENT	EXCELLENT	GOOD	EXCELLENT	GOOD
Corrosion Resistance	EXCELLENT	EXCELLENT	GOOD	EXCELLENT	EXCELLENT
Water Resistance	GOOD	GOOD	GOOD	EXCELLENT	EXCELLENT
Fungal Resistance	GOOD	GOOD	POOR	GOOD	GOOD
Sea Water	EXCELLENT	EXCELLENT	EXCELLENT	EXCELLENT	EXCELLENT
Chlorine Water	EXCELLENT	EXCELLENT	GOOD	EXCELLENT	EXCELLENT
Dark Cutting Oil	EXCELLENT	EXCELLENT	POOR	POOR	EXCELLENT
Cutting Fluid	EXCELLENT	EXCELLENT	POOR	EXCELLENT	POOR
Mek	GOOD	GOOD	POOR	POOR	POOR
Xylene	GOOD	GOOD	POOR	POOR	POOR
Surfuric Acid	POOR	POOR	EXCELLENT	EXCELLENT	EXCELLENT
Phosphoric Acid	POOR	POOR	EXCELLENT	EXCELLENT	EXCELLENT
Citric Acid	POOR	POOR	POOR	EXCELLENT	EXCELLENT

AUTOMOTIVE FLUID RESISTANCE

Unleaded Gasoline	EXCELLENT	EXCELLENT	POOR	POOR	POOR
Brake Fluid	GOOD	GOOD	POOR	POOR	EXCELLENT
Antifreeze	GOOD	GOOD	GOOD	GOOD	GOOD
Motor Oil	EXCELLENT	EXCELLENT	POOR	POOR	EXCELLENT