




# MOUNTING FOOT KIT FOR WFLP ENCLOSURES

(SCE-ELMFK6)



SEALING WASHERS  
(INCLUDED WITH  
WFLP ENCLOSURE)

RIGHT SIDE  
(SECTION VIEW)



PERFORMANCE CHARACTERISTICS 33% GLASS REINFORCED NYLON (POLYAMIDE 66)	
ACETIC ACID (DILUTED)	LITTLE EFFECT
ANTIFREEZE	NO EFFECT
BREAK FLUID	NO EFFECT
CHLORINE WATER	LITTLE EFFECT
CITRIC ACID (DILUTED)	LITTLE EFFECT
COLD	-40F
CORROSION RESISTANCE	EXCELLENT
DARK CUTTING OIL CUTTING FLUID	NO EFFECT
GASOLINE	NO EFFECT
HEAT RESISTANCE	>300F
IMPACT	EXCELLENT
MEK	NO EFFECT
MELTING POINT	504F
MOTOR OIL	NO EFFECT
SEA WATER	NO EFFECT
SULFURIC ACID (DILUTED)	LITTLE EFFECT
UL 94	V-2
UV RESISTANCE	EXCELLENT
WEATHER RESISTANCE	EXCELLENT
XYLENE	NO EFFECT
<b>STATIC LOAD</b>	
SCE-ELMFK6	1200 LBS.
SCE-ELMFK6SS	1200 LBS.

**MOUNTING FEET**

**NOT INTENDED FOR LIFTING.**

